



HEAD OFFICE: 41B OLUTOYE CRES. OFF ADENIYI JONES. IKEJA LAGOS
BRANCH OFFICE: KM 38, LEKKI/EPE EXPRESS WAY. LAKOWE. LAGOS
FOR ENQUIRIES; CALL: +234 812 085 5444 OR +234 808 955 2800
EMAIL: INFO@PSCSOLARUK.COM

Item No.	Photo	Features & Specifications		EXW Unit Price
IN-150W		Rated LED Power	150W, Bridgelux LED, 2800-6500K CCT available Max Lumens:15600-18000LM Light Distribution:Batwing Type II	240 (pcs)
		Solar Panel Capacity	18V 130W High Efficiency Monocrystalline more than 25 years warranty	
		Battery Capacity	Li-ion power battery 12V 96AH, 5 to 8 years lifespan	Mobile APP Remote Control - Switch the luminaire on and off remotely. - View the technical characteristics such as: Operating hours, battery voltage and temperature, solar panel voltage, etc - Identify malfunctions.
		PIR Sesnor	NO, 12 hrs with auto dim function	
		Solar Controller	Intelligent MPPT patent controller High conversion efficiency 91%	
		Light Body	Aluminum Alloy+Toughened Glass+Acrylic	Packing Details: 1. Carton size:1740x525x120mm, Mounting carton: 3905x215x315mm 2. N.W:26.5kg/G.W: 31.5kg 3. Qty: 1pc/2 cartons 4. 20GP: 200 Sets
		Installation Height	10 to 12 meters	
		Distance between Pole	30 to 36 meters	
		Solar Charging Time	6 to 7 hours by bright sunlight	
		Operating Temperature	-25° to 65°	Applications: Public Square/Plaza/Courtyard/Garden/Park/ Street/ Roadway/ Pathway/Parking Lot/Private/Road/ Sidewalk/Campus/ Airfield /Farm &Ranch /Perimeter Security/Wildlife Area/Military Base and so on.
Product Size	1670*450*45mm, Bracket 400*220*321mm			
Protection Grade	IP65			

Remark:

1. Above is EXW price without shipping charge and tax fee
2. Payment terms: Full payment before shipping
3. Warranty: 1 years for above items
4. Certificates: all our lamps approved with CE ROHS IP65 IES IEC ISO standards
5. All quotation exclude pole