


HEAD OFFICE: 41B OLUTOYE CRES. OFF ADENIYI JONES. IKEJA LAGOS Branch Office: KM 38, lekki/epe express way. lakowe. lagos For enquiries; call: +234 812 085 5444 or +234 808 955 2800 Email: INFO@PSCSOLARUK.COM







Quality Assurance



We provide 5 years of warranty since the date of inspection

ltem No.	Photo	Features & Specifications		EXW Unit Price
INH-150W		Rated LED Power	150W, Bridgelux LED, 2800-6500K CCT available Lumens: 15600-18000LM Light Distribution:Batwing Type II	300 (pcs)
		Solar Panel Capacity	18V 110W High Efficiency Monocrystalline more than 25 years warranty	
		Battery Capacity	Li-ion power battery 12V 72.8AH, 5 to 8 years lifespan	Mobile APP Remote Control - Switch the luminaire on and off remotely. - View the technical characteristics such as: Operating hours, battery voltage and temperature, solar panel voltage, etc - Identify malfunctions.
		MAX Sensing Distance	12M	
		Solar Controller	Intelligent MPPT patent controller; High conversion efficiency 91%	
		Light Body	100% die-cast aluminum	Packing Details: 1. Carton size:2025*425*380mm 2. N.W: 47.6 kg/G.W: 54kg 3. Qty: 2pcs/carton 4. 20GP: 80 cartons/160pcs
		Installation Height	10 to 12 meters	
		Distance between Pole	30 to 36 meters	
		Solar Charging Time	6 to 7 hours by bright sunlight	
		Operating Temperature	-25° to 65°	Applications: Public Square/Plaza/Courtyard/Garden/Park/Street/ Roadway/ Pathway/Parking Lot/Private/Road/ Sidewalk/Campus/ Airfield /Farm &Ranch /Perimeter Security/Wildlife Area/Military Base and so on.
		Product Size	1965*360*270mm	
		IP Grade	IP66	

Remark:

- 1. Above is EXW price without shipping charge and tax fee
- 2. Payment terms: Full payment before shipping
- 3. Warranty: 1 year for above items
- 4. Certificates: all our lamps approved with CE ROHS IP65 IES IEC ISO standards
- 5. All quotation exclude pole